

IN THE CLAIMS

Please amend the claims as follows:

1. (Currently amended) A system comprising:
a stimulus client, executing on a computer platform, configured to receive user input requesting an Internet Protocol (IP) telephony service and communicate the received user input over a packet-based network using a standard call control protocol; and
a call agent, executing on a remote server connected to the packet-based network, configured to perform the requested IP telephony service based on the received user input, wherein the received user input comprises Dual Tone Multi-Frequency (DTMF) input.
2. (Original) The system of claim 1 in which the stimulus client comprises an application layer configured to communicate with an end-user and a call control protocol stack configured to communicate with the call agent using the standard call control protocol.
3. (Original) The system of claim 2 in which the stimulus client's call control protocol stack comprises a Media Gateway Control Protocol (MGCP) stack.
4. (Original) The system of claim 2 in which the stimulus client's call control protocol stack comprises an ITU-T H.248 stack.
5. (Original) The system of claim 2 in which the application layer comprises a user interface having a plurality of graphical controls.
6. (Cancelled)
7. (Original) The system of claim 1 in which the call agent comprises:
a feature server configured to provide telephony services to telephony endpoints;

a signaling gateway configured to facilitate communication between the feature server and one or more endpoints; and

one or more call control protocol stacks configured to facilitate signaling between the call agent and the one or more endpoints.

8. (Currently amended) The system of claim 7 in which the feature server is configured to provide ~~capable of providing~~ supplementary services to one or more endpoints.

9. (Original) The system of claim 8 in which the supplementary services comprise ITU-T H.450 supplementary services.

10. (Original) The system of claim 7 in which the feature server provides non-standard telephony services to one or more endpoints.

11. (Original) The system of claim 7 in which one or more call control protocol stacks comprise one or more of a Media Gateway Control Protocol (MGCP) stack, an ITU-T H.248 stack, a Session Initiation Protocol (SIP) stack, and an ITU-T H.323 stack.

12. (Currently amended) A client system ~~application~~ comprising:
a client application residing on a computer platform, the client application comprising:
an application layer configured to receive Dual Tone Multi-Frequency (DTMF) input corresponding to a requested Internet Protocol (IP) telephony service; and
a call control protocol stack configured to communicate the received DTMF input to a feature server over a packet-based network using a standard call control protocol.

13. (Currently amended) The system ~~application~~ of claim 12 in which the application layer comprises a user interface having a plurality of graphic controls for receiving user input.

14. (Currently amended) The system ~~application~~ of claim 12 in which the call control protocol comprises a Media Gateway Control Protocol (MGCP).

15. (Currently amended) The system application of claim 12 in which the call control protocol comprises an ITU-T H.248 protocol.
16. (Currently amended) The system application of claim 12 in which the application includes substantially no software infrastructure for performing IP telephony services locally.
17. (Currently amended) The system application of claim 12 in which the application comprises a set of interpreted commands.
18. (Currently amended) The system application of claim 17 in which the application comprises an applet performed by a virtual machine.
19. (Currently amended) A method comprising:
 - in response to receiving user input requesting initiation of Internet Protocol (IP) telephony service, downloading and launching an IP telephony client application to a computer platform associated with the user;
 - receiving at the IP telephony client input from a user identifying a telephony service;
 - communicating the received input to a feature server; and
 - based on the communicated input, performing the identified telephony service at the feature server, wherein the received user input comprises Dual Tone Multi-Frequency (DTMF) input.
20. (Cancelled)
21. (Currently amended) The method of claim 19 in which downloading and launching an IP telephony client application comprises transparently downloading, from a user's perspective, a set of commands to be interpreted and performed by a process executing on a the computer platform associated with the user.

22. (Original) The method of claim 21 in which the set of commands comprises an applet to be performed by a virtual machine executing on the computer platform associated with the user.

23. (Original) The method of claim 19 in which the IP telephony client communicates with the feature server using a standard call control protocol.

24. (Original) Computer software, embodied in a computer-readable medium and/or a propagated carrier signal, comprising instructions for a computer system to perform the following:

present a telephony user interface that includes graphical controls for receiving input from a user;

receive from a user Dual Tone Multi-Frequency (DTMF) input corresponding to a requested IP telephony service; and

communicate the received DTMF input to a feature server over a packet-switched network using a standard call control protocol.

25. (Original) The software of claim 24 further comprising instructions to receive information from the feature server and use the received information to control elements of the telephony user interface.

26. (Original) The software of claim 24 in which the standard call control protocol comprises a stimulus protocol.

27. (Original) The software of claim 24 in which the standard call control protocol comprises a Media Gateway Control Protocol (MGCP).

28. (Original) The software of claim 24 in which the standard call control protocol comprises an ITU-T H.248 protocol.

29. (Original) The software of claim 24 in the instructions to communicate the received DTMF input to the feature server comprise a call control protocol stack.
30. (Original) The software of claim 24 further comprising instructions to receive user input requesting initiation of Internet Protocol (IP) telephony service and, in response to the received user input, download and launch an IP telephony client application.
31. (New) The system of claim 12 further comprising a pluggable call control (PCC) application program interface (API) configured to provide communication between the application layer and the call control protocol stack.